

**EDX 3202-S-HL**

Angular Contact Ball Bearing

**OVERVIEW****Boundary dimensions**

|                  |                |
|------------------|----------------|
| Bore diameter    | <b>15 mm</b>   |
| Outside diameter | <b>35 mm</b>   |
| Width            | <b>15.9 mm</b> |

**Properties**

|                                |                    |
|--------------------------------|--------------------|
| Number of rows                 | <b>2</b>           |
| Bore type                      | <b>Cylindrical</b> |
| Cage                           | <b>S-shaped</b>    |
| Radial internal clearance      | <b>CN</b>          |
| Tolerance class for dimensions | <b>P6</b>          |

**Performance**

|                           |                |
|---------------------------|----------------|
| Basic dynamic load rating | <b>12.5 KN</b> |
| Basic static load rating  | <b>7.9 KN</b>  |
| Limiting speed – Grease   | —              |
| Limiting speed – Oil      | —              |

**Additional specifications**

|               |                                                                  |
|---------------|------------------------------------------------------------------|
| bearing_image | <b>edx-3202-s-hl-double-row-angular-contact-ball-bearing.jpg</b> |
|---------------|------------------------------------------------------------------|

**Get in touch**

Sediu social: Bucuresti Sectorul 4,  
Bulevardul METALURGIEI, Nr 132, Bloc BIC, Etaj 4, Ap. 42.  
+40 723 370 345  
info@edxromania.ro

**Products & services**

- Ball Bearing
- Spherical Roller Bearing
- Cylindrical Roller Bearing
- Taper Roller Bearing