



## EDX 3324-M-C3

Angular Contact Ball Bearing

### OVERVIEW

#### Boundary dimensions

|                  |               |
|------------------|---------------|
| Bore diameter    | <b>120 mm</b> |
| Outside diameter | <b>260 mm</b> |
| Width            | <b>106 mm</b> |

#### Performance

|                           |                              |
|---------------------------|------------------------------|
| Basic dynamic load rating | <b>397.89999999999998 KN</b> |
| Basic static load rating  | <b>493.30000000000001 KN</b> |
| Limiting speed – Grease   | <b>800 r/min</b>             |
| Limiting speed – Oil      | <b>1400 r/min</b>            |

#### Properties

|                                |                    |
|--------------------------------|--------------------|
| Number of rows                 | <b>2</b>           |
| Bore type                      | <b>Cylindrical</b> |
| Cage                           | <b>Brass</b>       |
| Radial internal clearance      | <b>C3</b>          |
| Tolerance class for dimensions | <b>P6</b>          |

#### Additional specifications

|               |                                                                  |
|---------------|------------------------------------------------------------------|
| bearing_image | <b>edx-3324-m-c3-double-row-angular-contact-ball-bearing.jpg</b> |
|---------------|------------------------------------------------------------------|



#### Get in touch

Sediu social: Bucuresti Sectorul 4,  
Bulevardul METALURGIEI, Nr 132, Bloc BIC, Etaj 4, Ap. 42.  
+40 723 370 345  
info@edxromania.ro

#### Products & services

- Ball Bearing
- Spherical Roller Bearing
- Cylindrical Roller Bearing
- Taper Roller Bearing