



## EDX 3807-2Z-C3

Angular Contact Ball Bearing

### OVERVIEW

#### Boundary dimensions

|                  |              |
|------------------|--------------|
| Bore diameter    | <b>35 mm</b> |
| Outside diameter | <b>47 mm</b> |
| Width            | <b>10 mm</b> |

#### Performance

|                           |                    |
|---------------------------|--------------------|
| Basic dynamic load rating | <b>6.1 KN</b>      |
| Basic static load rating  | <b>6.2 KN</b>      |
| Limiting speed – Grease   | <b>8500 r/min</b>  |
| Limiting speed – Oil      | <b>10000 r/min</b> |

#### Properties

|                                |                     |
|--------------------------------|---------------------|
| Number of rows                 | <b>2</b>            |
| Bore type                      | <b>Cylindrical</b>  |
| Cage                           | <b>Nylon Sealed</b> |
| Radial internal clearance      | <b>C3</b>           |
| Tolerance class for dimensions | <b>P6</b>           |

#### Additional specifications

|               |                                                                   |
|---------------|-------------------------------------------------------------------|
| bearing_image | <b>edx-3807-2z-c3-double-row-angular-contact-ball-bearing.jpg</b> |
|---------------|-------------------------------------------------------------------|



#### Get in touch

Sediu social: Bucuresti Sectorul 4,  
Bulevardul METALURGIEI, Nr 132, Bloc BIC, Etaj 4, Ap. 42.  
+40 723 370 345  
info@edxromania.ro

#### Products & services

- Ball Bearing
- Spherical Roller Bearing
- Cylindrical Roller Bearing
- Taper Roller Bearing