

**EDX 3909-2Z**

Angular Contact Ball Bearing

**OVERVIEW****Boundary dimensions**

|                  |              |
|------------------|--------------|
| Bore diameter    | <b>45 mm</b> |
| Outside diameter | <b>68 mm</b> |
| Width            | <b>16 mm</b> |

**Performance**

|                           |                   |
|---------------------------|-------------------|
| Basic dynamic load rating | <b>17.9 KN</b>    |
| Basic static load rating  | <b>17.2 KN</b>    |
| Limiting speed – Grease   | <b>6000 r/min</b> |
| Limiting speed – Oil      | <b>6800 r/min</b> |

**Properties**

|                                |                     |
|--------------------------------|---------------------|
| Number of rows                 | <b>2</b>            |
| Bore type                      | <b>Cylindrical</b>  |
| Cage                           | <b>Nylon Sealed</b> |
| Radial internal clearance      | <b>CN</b>           |
| Tolerance class for dimensions | <b>P6</b>           |

**Additional specifications**

|               |                                                                |
|---------------|----------------------------------------------------------------|
| bearing_image | <b>edx-3909-2z-double-row-angular-contact-ball-bearing.jpg</b> |
|---------------|----------------------------------------------------------------|

**Get in touch**

Sediu social: Bucuresti Sectorul 4,  
Bulevardul METALURGIEI, Nr 132, Bloc BIC, Etaj 4, Ap. 42.  
+40 723 370 345  
info@edxromania.ro

**Products & services**

- Ball Bearing
- Spherical Roller Bearing
- Cylindrical Roller Bearing
- Taper Roller Bearing