

**EDX 3919-C3**

Angular Contact Ball Bearing

**OVERVIEW****Boundary dimensions**

|                  |               |
|------------------|---------------|
| Bore diameter    | <b>95 mm</b>  |
| Outside diameter | <b>130 mm</b> |
| Width            | <b>26 mm</b>  |

**Properties**

|                                |                    |
|--------------------------------|--------------------|
| Number of rows                 | <b>2</b>           |
| Bore type                      | <b>Cylindrical</b> |
| Cage                           | <b>Nylon</b>       |
| Radial internal clearance      | <b>C3</b>          |
| Tolerance class for dimensions | <b>P6</b>          |

**Performance**

|                           |                   |
|---------------------------|-------------------|
| Basic dynamic load rating | <b>32.6 KN</b>    |
| Basic static load rating  | <b>41.7 KN</b>    |
| Limiting speed – Grease   | <b>3000 r/min</b> |
| Limiting speed – Oil      | <b>3300 r/min</b> |

**Additional specifications**

|               |                                                                |
|---------------|----------------------------------------------------------------|
| bearing_image | <b>edx-3919-c3-double-row-angular-contact-ball-bearing.jpg</b> |
|---------------|----------------------------------------------------------------|

**Get in touch**

Sediu social: Bucuresti Sectorul 4,  
Bulevardul METALURGIEI, Nr 132, Bloc BIC, Etaj 4, Ap. 42.  
+40 723 370 345  
info@edxromania.ro

**Products & services**

- Ball Bearing
- Spherical Roller Bearing
- Cylindrical Roller Bearing
- Taper Roller Bearing