

**EDX HK1010**

Needle Roller Bearing

HK1010

**OVERVIEW****Boundary dimensions**

|                  |              |
|------------------|--------------|
| Bore diameter    | <b>10 mm</b> |
| Outside diameter | <b>14 mm</b> |
| Width            | <b>10 mm</b> |

**Performance**

|                           |                    |
|---------------------------|--------------------|
| Basic dynamic load rating | <b>3900 KN</b>     |
| Basic static load rating  | <b>4800 KN</b>     |
| Limiting speed - Grease   | <b>19000 r/min</b> |
| Limiting speed - Oil      | <b>15200 r/min</b> |

**Properties**

|                                |                |
|--------------------------------|----------------|
| Number of rows                 | <b>2</b>       |
| Bore type                      | <b>Special</b> |
| Cage                           | <b>Steel</b>   |
| Radial internal clearance      | <b>CN</b>      |
| Tolerance class for dimensions | <b>P6</b>      |

**Get in touch**

Sediu social: Bucuresti Sectorul 4,  
Bulevardul METALURGIEI, Nr 132, Bloc BIC, Etaj 4, Ap. 42.  
+40 723 370 345  
info@edxromania.ro

**Products & services**

- Ball Bearing
- Spherical Roller Bearing
- Cylindrical Roller Bearing
- Taper Roller Bearing