

**EDX NUP 1026 EM**

Cylindrical Roller Bearing

**OVERVIEW****Boundary dimensions**

|                  |               |
|------------------|---------------|
| Bore diameter    | <b>130 mm</b> |
| Outside diameter | <b>200 mm</b> |
| Width            | <b>33 mm</b>  |

**Performance**

|                           |             |
|---------------------------|-------------|
| Basic dynamic load rating | <b>191</b>  |
| Basic static load rating  | <b>238</b>  |
| Limiting speed – Grease   | <b>3200</b> |
| Limiting speed – Oil      | <b>4000</b> |

**Properties**

|                                |                    |
|--------------------------------|--------------------|
| Number of rows                 | <b>1</b>           |
| Bore type                      | <b>Cylindrical</b> |
| Cage                           | <b>Brass</b>       |
| Radial internal clearance      | <b>CN</b>          |
| Tolerance class for dimensions | <b>P6</b>          |

**Get in touch**

Sediu social: Bucuresti Sectorul 4,  
Bulevardul METALURGIEI, Nr 132, Bloc BIC, Etaj 4, Ap. 42.  
+40 723 370 345  
info@edxromania.ro

**Products & services**

- Ball Bearing
- Spherical Roller Bearing
- Cylindrical Roller Bearing
- Taper Roller Bearing