

## EDX NUP2216-EM-C3-P5

Cylindrical Roller Bearing



## OVERVIEW

## Boundary dimensions

|                  |          |
|------------------|----------|
| Bore diameter    | 95.3 mm  |
| Outside diameter | 127.3 mm |
| Width            | 3.8 mm   |

## Properties

|                                |             |
|--------------------------------|-------------|
| Number of rows                 | 1           |
| Bore type                      | Cylindrical |
| Cage                           | Brass       |
| Radial internal clearance      | C3          |
| Tolerance class for dimensions | P5          |

## Performance

|                           |         |
|---------------------------|---------|
| Basic dynamic load rating | 0 KN    |
| Basic static load rating  | 0 KN    |
| Limiting speed – Grease   | 0 r/min |
| Limiting speed – Oil      | 0 r/min |

## Additional specifications

|                       |                                                     |
|-----------------------|-----------------------------------------------------|
| bearing_image         | edx-NUP2216-EM-C3-P5-Cylindrical Roller Bearing.jpg |
| Reference Speed (rpm) | 4800                                                |
| Limiting Speed (rpm)  | 5600                                                |
| No. of Rollers        | 18                                                  |
| Bearing Grade         | GCr15                                               |
| Clearance (μm)        | 70-105                                              |
| Roller Length (mm)    | 24                                                  |
| Max Op.Temp (°C)      | 120                                                 |
| Weight (g)            | 1720                                                |



#### **Get in touch**

Sediu social: Bucuresti Sectorul 4,  
Bulevardul METALURGIEI, Nr 132, Bloc BIC, Etaj 4, Ap. 42.  
+40 723 370 345  
info@edxromania.ro

#### **Products & services**

- Ball Bearing
- Spherical Roller Bearing
- Cylindrical Roller Bearing
- Taper Roller Bearing