

EDX SI35T/K

Rod Ends Bearing

OVERVIEW

Boundary dimensions

Bore diameter	**35 mm**
Outside diameter	**43 mm**
Width	**43 mm**

Performance

Basic dynamic load rating	**101 KN**
Basic static load rating	**206 KN**
Limiting speed – Grease	**0 r/min**
Limiting speed – Oil	**0 r/min**

Properties

Number of rows	—
Bore type	—
Cage	—
Radial internal clearance	—
Tolerance class for dimensions	—

Additional specifications

Weight	**1.6 kg**
Outer Housing Thickness (C1)	**28 mm**
Spherical Ball Diameter (dK)	**57.1 mm**
Tilt Angle (α)	**16**
Internal Thread Size (G)	**M36 2**
Center-to-bottom shank height (h1)	**125 mm**
Min Thread engagement lengths (L3)	**56 mm**
Max Thread engagement lengths (L4)	**165.5 mm**
Keyway Width (b)	**0 mm**



Get in touch

Sediu social: Bucuresti Sectorul 4,
Bulevardul METALURGIEI, Nc 132, Bloc BIC, Etaj 4, Ap. 42.

+40 723 370 345
info@edxromania.ro

Products & services

- Ball Bearing
- Spherical Roller Bearing
- Cylindrical Roller Bearing
- Taper Roller Bearing

2026 © All Rights Reserved by Edx Rulmenti Romania S.R.L.