

# EDX SI5E

Rod Ends Bearing

## OVERVIEW

### Boundary dimensions

| | |
|---|---|
| Bore diameter | **5 mm** |
| Outside diameter | **21 mm** |
| Width | **6 mm** |

### Performance

| | |
|---|---|
| Basic dynamic load rating | **3.4 KN** |
| Basic static load rating | **8.1 KN** |
| Limiting speed – Grease | **0 r/min** |
| Limiting speed – Oil | **0 r/min** |

### Properties

| | |
|---|---|
| Number of rows | — |
| Bore type | — |
| Cage | — |
| Radial internal clearance | — |
| Tolerance class for dimensions | — |

### Additional specifications

| | |
|---|---|
| Weight | **0.023 kg** |
| Outer Housing Thickness ( C1 ) | **4.5 mm** |
| Spherical Ball Diameter ( dK ) | **10 mm** |
| Tilt Angle ( α ) | **13** |
| Internal Thread Size ( G ) | **M5** |
| Center-to-bottom shank height ( h1 ) | **30 mm** |
| Min Thread engagement lengths ( L3 ) | **11 mm** |
| Max Thread engagement lengths ( L4 ) | **40.5 mm** |
| Keyway Width ( b ) | **0 mm** |




**Get in touch**

Sediu social: Bucuresti Sectorul 4,
Bulevardul METALURGIEI, Nc 132, Bloc BIC, Etaj 4, Ap. 42.

+40 723 370 345
info@edxromania.ro

**Products & services**

- Ball Bearing
- Spherical Roller Bearing
- Cylindrical Roller Bearing
- Taper Roller Bearing

2026 © All Rights Reserved by Edx Rulmenti Romania S.R.L.